

EUROFLO[®] **CULVERT PIPE**

Made in Europe from HDPE (high density polyethylene), EUROFLO[®] is one of the strongest plastic pipes on the market.



EUROFLO® CULVERT PIPE

Made in Europe from HDPE (high density polyethylene), EUROFLO® is one of the strongest plastic pipes on the market.

BENEFITS

- Easy to handle
- Maintenance and rust free
- Ribbed exterior for strength
- Smooth bore for faster flow
- Resists chemically aggressive soil conditions
- Strong enough to handle a 50-tonne truck with 700mm of cover
- Socket one end

USES

- Farm culverts
- Forestry culverts
- Highway culverts
- Mine culverts
- Cut in 1/2 lengthways for stock troughs and fluming


Pipe Size (OD)	SN Rating	Code	SN Rating	Product Code
160mm	SN4	520-160-5.8M	-	-
200mm	SN4	520-200-5.8M	-	-
250mm	SN4	520-250-5.8M	SN8	560-250-5.8M
315mm	SN4	520-315-5.8M	SN8	560-315-5.8M
400mm	SN4	520-400-5.8M	SN8	560-400-5.8M
500mm	SN4	520-500-5.8M	SN8	560-500-5.8M
630mm	SN4	520-630-5.8M	SN8	560-630-5.8M
800mm	SN4	520-800-5.8M	SN8	560-800-5.8M
1000mm	SN4	520-1000-5.8M	SN8	560-1000-5.8M
1200mm	SN4	520-1200-5.8M	SN8	560-1200-5.8M
1300mm	-	-	SN8	560-1300-5.8M
1500mm	-	-	SN8	560-1500-5.8M
1700mm	-	-	SN8	560-1700-5.8M
1900mm	-	-	SN8	560-1900-5.8M
2100mm	-	-	SN8	560-2100-5.8M

EUROFLO® Slotted Pipe

allows you to fill in open drains without losing any ground drainage. Eliminate stock losses and comply with your environmental responsibilities to protect waterways.

5.8 metre lengths

Available in sizes from 160mm to 630mm diameter



Standard Pattern

**3-5 slots depending on size
Total slotted angle = 240°**

EUROFLO® Go-In System

is a fast and user-friendly, cost effective system that connects EUROFLO® pipe to sumps, galleries, breather pipes and main drains. Install branches after the main pipe has been placed and vertical installations can be done even when the water is flowing.



EUROFLO® Fittings available include rubbers, sealing adaptors, holesaw, sealing ring, reducers, bends and junctions.

Fluming socks.



Specifications

160mm – 1200mm stocked in 5.8m lengths, SN4 and SN8 rating.

1550mm – 2150mm stocked in 5.8m lengths, SN2 rating.

All sizes also available in SN16 rating upon request.