Tru-Test
DATAMARS

HD5T Load Bars

5,000 kg capacity

Tough, reliable and easy to install under your cattle crush.

Tru-Test load bars are recognised for their rugged durability and performance in harsh environments. The HD5T Load Bars are designed to be tough, reliable and easy to install under any crush. The simplicity of set up means you can easily install with no assistance needed.

With a capacity suitable for the heaviest of cattle crushes, you will have outstanding performance with the best weighing set up for your animals.

- ✓ **Extremely easy to install. Simply bolt it to the crush and then bolt to the level concrete surface.**
- ✓ **More capacity. The 5,000 kg capacity heavy duty load bar is suitable to mount under the heaviest of cattle crushes.**
- ✓ **Sealed load cell. Protects the load cell against moisture damage allowing the load bars to remain outside under the crush.**
- ✓ **Corrosion resistant. Galvanised steel construction means the HD5T Load Bars can endure the harshest agricultural environment.**
- ✓ **Robust. Heavy duty TPR/PVC cables are a standard feature, which minimise the likelihood of cable damage.**

How are you tracking?
Let's talk.
0800 55 33 11 (NZ)
1800 641 324 (AU)

SPECIFICATIONS

- ✓ **Total capacity**
  2 x HD5T load bars = 5,000 kg (11,000 lb)
- ✓ **Sensitivity**
  1.25 mV/V
- ✓ **Total nominal length**
  1115 mm
- ✓ **Weight (pair)**
  36 kg
- ✓ **Bar section width**
  75 mm
- ✓ **Overall height**
  110 mm
- ✓ **Cable length**
  5 m
- ✓ **Base resolution with Tru-Test scales**
  2 x HD5T load bars = 0.5 kg
- ✓ **Accuracy**
  +/- 1 % or 2 resolutions, whichever is greater

To view the dimension drawing, visit tru-test.com/HD5T.

Order Information

HD5T	Part No: 880 0000-565

Although the information presented in this Product Information Sheet is believed to be accurate and reliable, no responsibility for inaccuracies can be assumed by Datamars Limited. Performance data is typical only and variations due to component manufacturing tolerances are normal. Datamars Limited reserves the right at any time to change performance characteristics or specifications without prior notice. All trademarks with an * are not owned by Datamars and belong to their respective owners.
The Bluetooth® word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Datamars Limited is under licence. © Datamars Limited - All rights reserved.
3571TT02 Issue 3 10/20